

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description	Features
KEP210 is an EPDM rubber with very broad molecular weight distribution, medium ethylene, medium ENB contents. It can be used to LV/MV Electrical insulation, window seals, automobile parts, sponges and gasket.	- High vulcanization speed - Excellent roll processibility - Excellent extrusion properties - Good processing even without oil

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	23.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	64.5 ± 3.0	wt %	ASTM D3900
ENB Contents	5.7 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bag in Mesh Box, LDPE/HDPE film, 900 kg (25 kg × 36)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-1114
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2821
Revision Date	01/01/2025
Revision No.	13