

Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

Product Data Sheet

Product Description		Features	
KEP282F is an EPDM rubber with Medium molecular weight distribution, High ethylene , High ENB contents. It can be used to Weather strip solid, heat resistance hose, window seal, Various types of automobile parts.		- High loadability - High curing speed - Improved productivity & Collapse resistance - Suitable for weather strip solid	
Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 0.75	wt %	ASTM D5668
Mooney Viscosity ML(1+8)@125 °C	90.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	73.0 ± 2.0	wt %	ASTM D3900
ENB Contents	5.7 ± 1.0	wt %	ASTM D6047

Other Products Features

Product Form	Bale
Packaging	25 kg/Bale in Carton/Mesh Box, LDPE film, 750 kg (25 kg × 30)
Shelf Life	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
The Others	RoHS Free

Contact Information

Head Office	East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-1114
Plant	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2821
Revision Date	23/05/2024
Revision No.	7